



ProArt Display PA278CFRV



Key Features

QHD
2560x1440

Supporting QHD 2560 x 1440 resolution with IPS panel for crystal clear image quality

100Hz

Up to 100 Hz Variable Refresh Rate to optimize fast-rendering scenario



LuxPixel™ Technology with Anti-Glare, Low Reflection (AGLR) to reduce screen reflections and avoid disturbing your view

**95%
DCI-P3**

Provides brighter imagery and cinema-standard 95% DCI-P3 color gamut, guarantee ΔE color difference less than 2



USB Type-C
Monitor

Full function USB-C connection for DisplayPort video, USB data transmission and supports 96W power delivery



Ambient Light
Sensor

Ambient Light Sensor to synchronizes display brightness and color temperature with environment light changes



Daisy-chain

DisplayPort allows users to daisy chain up to 4 monitors for a multi-display workstation from one video source



USB Hub

Embedded four USB ports for connecting mouse, keyboard, or other USB devices



4-way Ergonomic
Stand

Ergonomically-designed stand with tilt, swivel, pivot, and height adjustments

ASUS

ProArt Display PA278CFRV

Spec Sheet

Display	Panel Size (inch) : 27 (16:9) Pixels Per Inch (PPI) : 109 Display Viewing Area (H x V) : 596.74 x 335.66 mm Display Surface : AGLR (Anti-Glare, Low-Reflection) Panel Type : IPS Viewing Angle (CR≥10, H/V) : 178° / 178° Pixel Pitch : 0.2331mm Resolution : 2560x1440 Color Space (sRGB) : 100% Color Space (DCI-P3) : 95% Brightness (HDR, Peak) : 400 cd/m² Brightness (Typ.) : 350cd/m² Contrast Ratio (Dynamic) : 3000:1 Contrast Ratio (Typ.) : 1000:1 Display Colors : 16.7M Response Time : 5ms (GTG) Refresh Rate (Max) : 100Hz HDR (High Dynamic Range) Support : HDR10 Flicker-free : Yes LCD ZBD Warranty : Yes (3 year)
Video Feature	ProArt Preset : Native / sRGB / Rec. 709 / DCI-P3 / Adobe RGB / Rec. 2020 / DICOM / HDR / User Mode 1 / User Mode 2 Color Temp. Selection : Yes (5 modes) Gamma Adjustment : Yes (Support Gamma 1.8 / 2.0 / 2.2 / 2.4 / 2.6) Color Accuracy : ΔE< 2 ProArt Palette : Yes QuickFit Plus : Yes PIP / PBP Technology : Yes HDCP : Yes, 2.2 VRR Technology : Yes, Adaptive-Sync ProArt Chroma Tune : Yes DisplayWidget : Yes, DisplayWidget Center Low Blue Light : Yes
Audio Feature	Speaker : Yes (2Wx2)
IO ports	USB-C x 1 (DP Alt Mode) DisplayPort 1.4 x 2 (Daisy Chain) HDMI (v2.0) x 1 USB-C Power Delivery : 96W USB Hub : Yes (USB 3.2 Gen 1 Type-C; USB 3.2 Gen 1 Type-A x 3) Earphone Jack : Yes
Signal Frequency	Digital Signal Frequency : 15~155 KHz (H) / 48~100 Hz (V)
Power Consumption	Power On (Typical): <16W* Power Saving Mode : <0.5W ; Power Off Mode : 0W (Hard Switch) 100~240V, 50/60Hz
Mechanical Design	Tilt : Yes (+23° ~ -5°) Swivel : Yes (+30° ~ -30°) Pivot : 90° (Clockwise& Anticlockwise) Ambient Light Sensor : Yes Height Adjustment : 0~130mm VESA Wall Mounting : 100x100mm Kensington Lock : Yes
Dimensions (Est.)	Phys. Dimension (W x H x D) : 61.33 x 53.67 x 19.72 cm (24.15" x 21.13" x 7.76") Phys. Dimension without Stand (W x H x D) : 61.33 x 36.34 x 4.49 cm (24.15" x 14.31" x 1.77") Box Dimension (W x H x D) : 69.5 x 42.1 x 13.3 cm (27.36" x 16.57" x 5.24")
Weight (Est.)	Net Weight : 6.6 kg (14.5 lbs) Net Weight without Stand : 4.9 kg (10.08 lbs) Gross Weight : 9.0 kg (19.8 lbs)
Accessories	Power cord, USB-C cable (optional), HDMI cable (optional), DisplayPort cable (optional), Calibration Report, Quick Start Guide, Warranty Card, Welcome Card
Compliance Standard	FCC, UL/cUL, ICES-3, CB, CE, ErP, WEEE, ISO 9241-307, UkrSEPRO., CU, BSMI, RCM, AU MEPS, VCCI, PSE, PC Recycle, J-MOSS, KC, KCC, SDoC, KMEPS, PSB, VN MEPS, Energy Star®, TCO, RoHs, CEC, WHQL Windows 10/11, Halogen Free, EPEAT Gold, TÜV Flicker Free, TÜV Low Blue Light, VESA DisplayHDR 400, VESA MediaSync Display, Calman Verified, Mac compliance

*Power consumption is measured with screen brightness of 200 nits without audio / USB / or other peripheral connections drawing power.

**All specifications are subject to change without notice

ASUS